



F121 Single Console

1080p
Full HD



Drawer Features & Display Benefits

- ▶ 1U 21" widescreen LCD console drawer
- ▶ Support Full HD with 1080p resolution
- ▶ 104-key keyboard with either touchpad or trackball
- ▶ SUN Micro or MAC keyboard options available
- ▶ New enhanced aesthetics with molded front handle
- ▶ Front USB port for device access (USB Hub KVM only)

Options

- 3G / HD / SD-SDI Broadcast-grade input (w/ speaker)
- HDMI (w/ speaker)
- DC power : 12V / 24V / 48V / 110 ~ 125V

Ordering Information	Standard (left side open)	Option (right side open)
Model	F121	F121R

Specifications

• LCD Panel

Manufacturer : **AUO**
 Size (diagonal) : 21.5" widescreen TFT
 Max resolution : 1920 x 1080
 Brightness (cd/m2) : 250
 Backlight : LED
 Colors : 16.7 M
 Contrast ratio (typ) : 1000 : 1
 Viewing angle (H/V) : 170° x 160°
 Active area (mm) : 477 x 268
 MTBF (hrs) : 30,000
 Video input : Standard - DVI-D
 Option - HDMI (bundle speaker x 2)

• **Speaker :** Built-in Dual Stereo Speakers
(HDMI only) 2W x 2

• **Casing Color :** Black (RAL 9005)

• **Power Input :** Auto-sensing 100 to 240VAC,
50 / 60Hz

• Power Consumption (single console)

Sreen on : Max. 32W
 Power saving mode : Max. 4W
 Power button on : Max. 1W

• Environmental

Operating temperature : 0 to 55°C degree
 Storage temperature : -20 to 60°C degree
 Operating humidity : 20~90%, non-condensing
 Storage humidity : 5 ~90%, non-condensing
 Operating altitude : 16,000 ft
 Non-operating altitude : 40,000 ft
 Shock : 10G acceleration (11ms duration)
 Vibration : 5~500Hz 1G RMS random vibration

• Regulatory

Safety : FCC & CE certified
 Environmental : RoHS2 & REACH compliant

• Weight (single console)

Net : 14.7 kgs / 32.3 lbs
 Gross : 18.9 kgs / 41.6 lbs

• Dimensions (single console)

Product : 441.6 x 670 x 44 mm / 17.4 x 26.4 x 1.73 inch
 Packing : 595 x 860 x 140 mm / 23.4 x 33.9 x 5.5 inch


Console Cable

CX-6


6 feet DVI-D console cable (bundle)
 - DVI-D + USB, server end
 - DVI-D + DB15 (USB KB & MS),
 console port

Standard Keyboard

Ge G keyboard integrated with touchpad



Gb G keyboard integrated with trackball



Keyboard Options

* US layout only

Me Mac keyboard with touchpad



Mb Mac keyboard with trackball

Se S keyboard with touchpad

Sb S keyboard with trackball



Supporting layouts

America	United States
EMEA	United Kingdom Germany France Spain Norway Italy Russia Switzerland Netherlands Portugal
Asia	China Japan Korea Arabia Turkey

1U 21" FHD LCD KVM Drawer



- Dimensions (with KVM)**
 Product : 441.6 x 770 x 44 mm / 17.4 x 30.3 x 1.73 inch
 Packing : 595 x 860 x 140 mm / 23.4 x 33.9 x 5.5 inch
 - Weight**
 Net : 15.5 kgs / 34.1 lbs
 Gross : 21.4 kgs / 47.1 lbs
 - Power Consumption with KVM integration :**
 Screen on : Max. 62W
 Power saving mode : Max. 34W
 - Casing Color :** Black (RAL 9005)
- * For details, please refer to our KVM rear kit user manuals.

www.austin-hughes.com/support/usermanual/cyberview/UM-CV-MUKVM-KIT.pdf

For right side open - Add **R** at the end of the model no.
sample : F121-MUIP3224R

Matrix Cat6 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	1	1	-	F121 - MUIP1613	F121 - MUIP3213
	1	1	2	-	F121 - MUIP1624	F121 - MUIP3224
	1	1	0	-	F121 - MU1602	F121 - MU3202
	1	2	0	-	F121 - MU1603	F121 - MU3203
	1	3	0	-	F121 - MU1604	F121 - MU3204

www.austin-hughes.com/support/usermanual/cyberview/UM-CV-UKVM-KIT.pdf

Combo Cat6 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	0	1	F121 - UIP802	F121 - UIP1602	F121 - UIP3202
	1	1	0	F121 - U802	F121 - U1602	F121 - U3202
	1	0	0	F121 - U801	F121 - U1601	F121 - U3201

Cat6 KVM Dongle : DG-100S (VGA-USB) / DG-100 (VGA-PS/2) / DG-100SD (DVI-USB)

www.austin-hughes.com/support/usermanual/cyberview/UM-CV-MKVM-KIT.pdf

For right side open - Add **R** at the end of the model no.
sample : F121-S1601R

Matrix DB-15 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	1	1	F121 - MIP813	F121 - MIP1613	-
	1	1	2	F121 - MIP824	F121 - MIP1624	-
	1	1	0	F121 - M802	F121 - M1602	-
	1	2	0	F121 - M803	F121 - M1603	-
	1	3	0	F121 - M804	F121 - M1604	-

www.austin-hughes.com/support/usermanual/cyberview/UM-CV-SKVM-KIT.pdf

Combo DB-15 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	0	1	F121 - IP802	F121 - IP1602	-
	1	1	0	F121 - 802	F121 - 1602	-
	1	0	0	F121 - S801	F121 - S1601	-

Combo DB-15 KVM Cable : CE-6 / 10 / 15 (6, 10 or 15 ft)

www.austin-hughes.com/support/usermanual/cyberview/UM-CV-DVIKVM-KIT.pdf

For right side open - Add **R** at the end of the model no.
sample : F121-1201DR

DVI-D KVM	Local	Remote	IP	12-port	-	-
	1	0	0	F121 - 1201D	-	-

DVI-D KVM Cable : CI-6 / 15 (6 or 15 ft)

www.austin-hughes.com/support/usermanual/cyberview/UM-CV-USBKVM-KIT.pdf

For right side open - Add **R** at the end of the model no.
sample : F121-801HR

USB Hub DB-15 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	0	1	F121 - IP802H	F121 - IP1602H	-
	1	1	0	F121 - 802H	F121 - 1602H	-
	1	0	0	F121 - 801H	F121 - 1601H	-

USB KVM Cable : CB-6 / 10 / 15 (6, 10 or 15 ft)