

### RP-120




#### Drawer Features & Display Benefits

- ▶ 1U 20" LCD drawer with DVI-D / VGA input
- ▶ 1600 x 1200 high resolution
- ▶ Sliding LCD allowing LCD to remain open when the rack door is closed
- ▶ Enhanced aesthetics with molded front panel and two point lock

#### Options

- 3G / HD / SD-SDI Broadcast-grade input
- S-Video + Composite ( BNC )
- HDMI or Audio input
- DC power : 12V / 24V / 48V / 110 ~ 125V




Basic I/O : VGA and DVI-D

Options : HDMI, Audio, S-Video + BNC

#### Specifications

##### • LCD Panel

Manufacturer :	
Size (diagonal) :	20.1" TFT
Max resolution :	1600 x 1200
Brightness (cd/m2) :	300
Backlight :	CCFL
Colors :	16.7 M
Contrast ratio (typ) :	800 : 1
Viewing angle (H/V) :	178° x 178°
Active area (mm) :	408 x 306
MTBF (hrs) :	45,000
Signal input :	VGA or DVI-D

• **Speaker :** Built-in Dual Stereo Speakers ( option ) 2W x 2

• **Power Input :** Auto-sensing 100 to 240VAC, 50 / 60Hz

##### • Power Consumption

Sreen on :	Max. 48W
Power saving mode :	Max. 4W
Power button on :	Max. 1W

##### • Environmental

Operating temperature :	0 to 55°C degree
Storage temperature :	-20 to 60°C degree
Operating humidity :	20~90%, non-condensing
Storage humidity :	5 ~90%, non-condensing
Operating altitude :	16,000 ft
Non-operating altitude :	40,000 ft
Shock :	10G acceleration ( 11ms duration )
Vibration :	5~500Hz 1G RMS random vibration

• **Casing Color :** Black ( RAL 9005 )

##### • Regulatory

Safety :	FCC & CE certified
Environmental :	RoHS2 & REACH compliant

##### • Weight

Net :	13.5 kgs / 29.7 lbs
Gross :	17.5 kgs / 38.5 lbs

##### • Dimensions

Product :	439.6 x 650 x 44 mm / 17.3 x 25.6 x 1.73 inch
Packing :	595 x 860 x 140 mm / 23.4 x 33.9 x 5.5 inch

#### Diagrams ( mm )

