




Benefits

- ▶ 9U 19" LCD Quad display panel
- ▶ 1280 x 1024 native resolution / 16.7M colors
- ▶ VGA + Quad Display (Composite BNC x 4) video input
- ▶ 2-year standard warranty (upgradable up to 5 years)

Options

- DC power : 12V / 24V / 48V / 125V

RP-W819QD



Product Specifications

Video	
Video input	QD (Composite BNC x 4) + VGA

LCD Panel	
Panel size (diagonal)	19"
Native resolution	1280 x 1024
Brightness (cd/m ²)	250
Contrast ratio (typ.)	1000 : 1
Colors	16.7 M
Viewing angle (L/R/U/D)	85/85/80/80
Response time (ms)	5
Dot pitch (mm)	0.294
Display area (mm)	376.32H x 270.33V
Surface treatment	Haze 25%, Hard-coating
Surface hardness	3H
Backlight type	LED
MTBF (hrs)	30,000

Power		
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption	Screen on	Max. 25W
	Power saving mode	Max. 4W
	Power button off	Max. 1W

Environment	
Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	20-90%, non-condensing
Storage humidity	5 -90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration (11ms duration)
Vibration	10-300Hz 0.5G RMS random vibration

Compliance	
EMC	FCC & CE certified
Safety	CE / LVD certified
Environment	RoHS2 & REACH compliant

Physical		
Dimensions (W x D x H)	Product	480 x 69 x 399 mm
	Packing	18.9 x 2.7 x 15.7 inch
Weight	Net	583 x 124 x 529 mm
	Gross	23 x 4.9 x 20.8 inch
	Net	9.5 kg / 20.9 lb
	Gross	12.5 kg / 27.5 lb

* All dimensions stated are subject to change if options are selected / integrated to base model part codes

Diagrams (mm)

