

RP-F117



1080p
Full HD


FC CE RoHS REACH

Drawer Features & Display Benefits

- ▶ 1U 17" widescreen LCD drawer with DVI-D / VGA input
- ▶ Support **Full HD** with 1080p resolution
- ▶ Green LED-backlit panel technology
- ▶ Enhanced aesthetics with molded front panel and two point lock
- ▶ Short depth design of 480mm (18.9") only

Options

- 3G / HD / SD-SDI Broadcast-grade input (w/ speaker)
- F17" Touchscreen : Resistive
- HDMI (w/ speaker) or Audio input
- DC power : 12V / 24V / 48V / 110 ~ 125V



Basic I/O : VGA and DVI-D

Options : HDMI w/ speaker, Audio SDI w/ speaker, USB for touchscreen

** For the above options, casing depth will be extended from 480mm (18.9") to 530mm (20.9")

Specifications

• LCD Panel

Size (diagonal) :	17.3" widescreen TFT
Max resolution :	1920 x 1080
Brightness (cd/m2) :	400
Backlight :	LED
Colors :	16.7 M, 8-bit
Contrast ratio (typ) :	600 : 1
Viewing angle (H/V) :	160° x 140°
Active area (mm) :	382 x 215
MTBF (hrs) :	50,000
Signal input :	VGA or DVI-D

• **Speaker :** Built-in Dual Stereo Speakers
(option) 2W x 2

• **Power Input :** Auto-sensing 100 to 240VAC, 50 / 60Hz

• Power Consumption

Sreen on :	Max. 25W
Power saving mode :	Max. 4W
Power button on :	Max. 1W

• Environmental

Operating temperature :	0 to 55°C degree
Storage temperature :	-20 to 60°C degree
Operating humidity :	20~90%, non-condensing
Storage humidity :	5 ~90%, non-condensing
Operating altitude :	16,000 ft
Non-operating altitude :	40,000 ft
Shock :	10G acceleration (11ms duration)
Vibration :	5~500Hz 1G RMS random vibration

• **Casing Color :** Black (RAL 9005)

• Regulatory

Safety :	FCC & CE certified
Environmental :	RoHS2 & REACH compliant

• Weight

Net :	11 kgs / 24.2 lbs
Gross :	15 kgs / 33 lbs

• Dimensions

Product :	441.6 x 480 x 44 mm / 17.4 x 18.9 x 1.73 inch
Packing :	588 x 758 x 120 mm / 23.1 x 29.8 x 4.7 inch

Diagrams (mm)

