

RP-F617

1080p
Full HD




Display Features & Benefits

- ▶ 6U rackmount 17" widescreen LCD
- ▶ Support **Full HD** with 1080p resolution
- ▶ Green LED-backlit panel technology
- ▶ Ideal for CCTV security & industrial control

Options

- 3G / HD / SD-SDI Broadcast-grade input (w/ speaker)
- **MCS** Multi-display control solution
- F17" Touchscreen : Resistive
- S-Video + Composite (BNC)
- HDMI or Audio input
- DC power : 12V / 24V / 48V / 110 ~ 125V
- MIL-type or lockable connector



- Basic I/O** : DVI-D + VGA
- AV3.0 upgrade** : DVI-D + VGA + HDMI + BNC + S-Video + audio
- Options** : SDI, USB for touchscreen & DC power

Specifications

• LCD Panel

- Size (diagonal) : 17.3" widescreen TFT
- Max resolution : 1920 x 1080
- Brightness (cd/m2) : 400
- Backlight : LED
- Colors : 16.7 M, 8-bit
- Contrast ratio (typ) : 600 : 1
- Viewing angle (H/V) : 160° x 140°
- Active area (mm) : 382 x 215
- MTBF (hrs) : 50,000
- Signal input : VGA or DVI-D

- **Speaker** : Built-in Dual Stereo Speakers
2W x 2

- **Power Input** : Auto-sensing 100 to 240VAC, 50 / 60Hz

• Power Consumption

- Screen on : Max. 25W
- Power saving mode : Max. 4W
- Power button on : Max. 1W

• Environmental

- Operating temperature : 0 to 55°C degree
- Storage temperature : -20 to 60°C degree
- Operating humidity : 20~90%, non-condensing
- Storage humidity : 5 ~90%, non-condensing
- Operating altitude : 16,000 ft
- Non-operating altitude : 40,000 ft
- Shock : 10G acceleration (11ms duration)
- Vibration : 5~500Hz 1G RMS random vibration

- **Casing Color** : Black (RAL 9005)

• Regulatory

- Safety : FCC & CE certified
- Environmental : RoHS2 & REACH compliant

• Weight

- Net : 4.5 kgs / 9.8 lbs
- Gross : 6 kgs / 13.2 lbs

• Dimensions

- Product : 480 x 48 x 266 mm / 18.9 x 1.9 x 10.5 inch
- Packing : 529 x 124 x 451 mm / 20.8 x 4.9 x 17.8 inch

Diagrams (mm)

