

RP-W119




Drawer Features & Display Benefits

- ▶ 1U 19" widescreen LCD drawer with DVI-D / VGA input
- ▶ Short depth design of 460mm (18.1")
- ▶ Green LED-backlit panel technology
- ▶ Sliding LCD allowing LCD to remain open when the rack door is closed
- ▶ Enhanced aesthetics with molded front panel and two point lock

Options

- 3G / HD / SD-SDI Broadcast-grade input
- S-Video + Composite (BNC)
- HDMI or Audio input
- DC power : 12V / 24V / 48V / 110 ~ 125V



Basic I/O : VGA and DVI-D

**Options : HDMI, Audio, S-Video + BNC
SDI**

** For the above options, casing depth will be extended from 460mm (18.1") to 530mm (20.9")

Specifications

• LCD Panel

Manufacturer :	
Size (diagonal) :	19" widescreen TFT
Max resolution :	1440 x 900
Brightness (cd/m ²) :	300
Backlight :	CCFL
Colors :	16.7M
Contrast ratio (typ) :	1000 : 1
Viewing angle (H/V) :	160° x 160°
Active area (mm) :	408 x 255
MTBF (hrs) :	50,000
Signal input :	VGA or DVI-D

• **Speaker :** Built-in Dual Stereo Speakers
(option) 2W x 2

• **Power Input :** Auto-sensing 100 to 240VAC, 50 / 60Hz

• Power Consumption

Sreen on :	Max. 25W
Power saving mode :	Max. 4W
Power button on :	Max. 1W

• Environmental

Operating temperature :	0 to 55°C degree
Storage temperature :	-20 to 60°C degree
Operating humidity :	20~90%, non-condensing
Storage humidity :	5 ~90%, non-condensing
Operating altitude :	16,000 ft
Non-operating altitude :	40,000 ft
Shock :	10G acceleration (11ms duration)
Vibration :	5~500Hz 1G RMS random vibration

• **Casing Color :** Black (RAL 9005)

• Regulatory

Safety :	FCC & CE certified
Environmental :	RoHS2 & REACH compliant

• Weight

Net :	13 kgs / 28.6 lbs
Gross :	17 kgs / 37.4 lbs

• Dimensions

Product :	441.6 x 460 x 44 mm / 17.4 x 18.1 x 1.73 inch
Packing :	588 x 758 x 120 mm / 23.1 x 29.8 x 4.7 inch

Diagrams (mm)

